

Project:



Scan for more info!

Owners manual
Quick install
Quick sizing
Install layout
Parts list

CR-2PB Countertop Push Button




Sparkling & chilled water on tap

- Cold carbonation for better long lasting sparkling water
- Push button dispensing; ideal for self-service use
- European design, mirrored finish stainless steel exterior
- Available in 3 valve configuration for ambient temperature water

Specifications

- 80 liters per hour @ <40°
- Self-contained refrigeration system
- Compressor: 1/3 H.P.
- Refrigerant: R134a CFC-free
- BTU: 2,600 per hour Ave
- Operating temperature range: 40°-100°
- Electrical: 120v - 15 Amps
- Carbonator: 1/3 H.P.
- Water Bath: 6 Gallons
- Ice Bank: 25 lbs
- Weight: 165 lbs
- Clearance: 11"
- 20"W x 26"D x 24.75"H



- 3/8" Water inlet connector
- 7' Over flow drain hose
- 7' CO2 hose 1/4" flare fitting
- 9' Electrical cord NEMA 5-15
- 4.25" legs
- Air intake at rear with air filter
- Allow for 6" rear & side clearance around unit for air flow
- Drip Drain Pan: 1/2" barb fitting

Accessories:

- CR-24FCP with Prefilter
 - CR-24FC without Prefilter
- Twin filter system with compact fibredyne filters, 19"H x 17"W 5 gpm, 30,000 gal, TOC & 1/2 micron filtration



- CR-KIT-CT
- Installation kit for countertop units, CR-1 & CR-2, Includes: water pressure reducer valve, fittings and oetiker clamps and extra tubing to install the filter systems and countertop unit



- CR-3741
- Primary high pressure CO2 regulator for CO2 tank



- Customer supplied CO2 tank required

