



# Beverage Run Rise Charts

FOR T5000 AND G55 PUMPS

**FLOJET**

a xylem brand

# G55 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700	800	900	1000
0	51	53	57	61	65	70	74	82	90					
	50	51	52	54	55	57	58	61	64	67	70	73	76	80
10	56	58	62	66	70	75	79	87						
	55	56	57	59	60	62	63	66	69	72	75	78	81	85
20	61	63	67	71	75	80	84							
	60	61	62	64	65	67	68	71	74	77	80	83	86	90
30		68	72	76	80	85	89							
		66	67	69	70	72	73	76	79	82	85	88		
40		73	77	81	85	90								
		71	72	74	75	77	78	81	84	87	90			
50		78	82	86	90									
		76	77	79	80	82	83	86	89					
60			87											
			82	84	85	87	88							

### Conversions:

#### Feet to Meters:

Multiply by .3048

#### PSI to BAR:

Multiply by .06895

# G55 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	350	400	500	600	700	800	900	1000
0	49	51	53	56	58	61	64	66	69	74	79	84	90		
10	48	49	49	50	50	51	51	52	53	54	55	56	57	58	60
	54	56	58	61	69	66	69	71	74	79	84	89			
	53	54	54	55	55	56	56	57	58	59	60	61	62	63	65
20	59	61	63	66	68	71	74	76	79	84	89				
	58	59	59	60	60	61	61	62	63	64	65	66	67	68	70
30		66	68	71	73	76	79	81	84	89					
		64	64	65	65	66	66	67	68	69	70	71	72	73	75
40		71	73	76	78	81	84	86	89						
		69	69	70	70	71	71	72	73	74	75	76	77	78	80
50		76	78	81	83	86	89								
		74	74	75	75	76	76	77	78	79	80	81	82	83	85
60			83	86	88										
			79	80	80	81	81	82	83	84	85	86	87	88	90

### Conversions:

#### Feet to Meters:

Multiply by .3048

#### PSI to BAR:

Multiply by .06895

# G55 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700	800	900	1000
0	52	54	60	65	70	76	81							
	50	57	59	55	56	58	60	64	68	71	75	79	82	86
10	57	59	65	70	75	81	86							
	55	56	58	60	61	63	65	69	73	76	80	84	87	
20	62	64	70	75	80	86								
	60	61	63	65	66	63	70	74	78	81	85	89		
30		69	75	80	85									
		66	68	70	71	73	75	79	83	86	90			
40		74	80	85	90									
		71	73	75	76	78	80	84	88					
50		79	85	90										
		76	78	80	81	83	85	89						
60			90											
			83	85	86	88	90							

### Conversions:

#### Feet to Meters:

Multiply by .3048

#### PSI to BAR:

Multiply by .06895

# G55 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700	800	900	1000
0	50	52	55	59	63	67	70	78	85					
	49	49	50	52	53	54	55	58	60	62	65	67	70	72
10	55	57	60	64	68	72	75	83	90					
	54	54	55	57	58	59	60	63	65	67	70	72	75	77
20	60	62	65	69	73	77	80	88						
	59	59	60	62	63	64	65	68	70	72	75	77	80	82
30		67	70	74	78	82	85							
		64	65	67	68	69	70	73	75	77	80	82	85	87
40		72	75	79	83	87	90							
		69	70	72	73	74	75	78	80	82	85	87	90	
50		77	80	84	88									
		74	75	77	78	79	80	83	85	87	90			
60			85	89										
			80	82	83	84	85	88	90					

**Conversions:**  
**Feet to Meters:**  
 Multiply by .3048  
**PSI to BAR:**  
 Multiply by .06895

# T5000 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700	800	900
0	54	56	60	64	68	73	77						
10	53	54	55	57	58	60	61	64	67	70	73	76	79
20	59	61	65	69	73	78							
30	58	59	60	62	63	65	66	69	72	75	78		
40	64	66	70	74	78								
50	63	64	65	67	68	70	71	74	77	80			
		71	75	79									
		69	70	72	73	75	76	79					
		76	80										
		74	75	77	78	80							
		79	80										

### Conversions:

**Feet to Meters:**

Multiply by .3048

**PSI to BAR:**

Multiply by .06895

# T5000 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Medium Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700	800	900	1000
0	51	53	55	58	60	63	66	71	76					
10	50	51	51	52	52	53	53	55	56	57	58	59	60	62
20	61	63	65	68	70	73	76							
30	60	61	61	62	62	63	63	65	66	67	68	69	70	72
40		68	70	73	75	78								
50		66	66	67	67	68	68	70	71	72	73	74	75	
		73	75	78	80									
		71	71	72	72	73	73	75	76	77	78	79		
		78	80											
		76	76	77	77	78	78	80						

### Conversions:

#### Feet to Meters:

Multiply by .3048

#### PSI to BAR:

Multiply by .06895

# T5000 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Fast Flow Valve - 4.5 oz/sec (.75 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700
0	55	57	63	68	73	79					
	53	54	56	58	59	61	63	67	71	74	78
10	60	62	68	73	78						
	58	59	61	63	64	66	68	72	76	79	
20	65	67	73	78							
	63	64	66	68	69	71	76	77			
30		72	78								
		69	71	76	74	76	78				
40		77									
		74	76	78	79						
50											
											79

### Conversions:

#### Feet to Meters:

Multiply by .3048

#### PSI to BAR:

Multiply by .06895

# T5000 Series Pumps - Run/Rise Charts

CO<sub>2</sub> Regulator Settings for B-I-B Pump Installation

## Heavy Syrups

1. Select vertical syrup tubing rise (ft) from left hand side of chart.
2. Select total tubing syrup run (ft) across top of chart.
3. Read regulator setting (psi) from chart.

To produce 40 PSI to dispenser.

A	< Reading for 3/8" tubing
B	< Reading for 1/2" tubing

## One Standard Flow Valve - 3.0 oz/sec (.5 oz/sec of syrup)

Total Run (ft) - Vertical & Horizontal

	25	50	100	150	200	250	300	400	500	600	700	800	900	1000
0	52	54	57	61	65	69	72	80						
10	51	51	52	54	55	56	57	60	62	64	67	69	72	74
20	57	59	62	66	70	74	77							
30	56	56	57	59	60	61	62	65	67	69	72	74	77	79
40	62	64	67	71	75	79								
50	61	61	62	64	65	66	67	70	72	74	77	79		
		69	72	76	80									
		66	67	69	70	71	72	75	77	79				
		74	77											
		71	72	74	75	76	77	80						
		79												
		76	77	79	80									

### Conversions:

**Feet to Meters:**

Multiply by .3048

**PSI to BAR:**

Multiply by .06895



Xylem

17942 Cowan

Irvine, CA 92614

Tel +1.949.608.3900

Fax +1.949.609.3887

[www.xylemflowcontrol.com](http://www.xylemflowcontrol.com)

Flojet is a trademark of Xylem Inc. or one of its subsidiaries.

© 2012 Xylem, Inc. 950-0616 Rev B. 1/12